



Elevation Innovation Inc.
6048 Enterprise Dr Suite A
Diamond Springs, CA 95619
Phone: 530-295-4900
Fax: 877-285-3050

Inteli-Lift 250 Dumbwaiter Specifications

UL Listing #SA32120

| | |
|---------------------------|--|
| DEFLECTION | 250# dumbwaiter will carry 250 lbs and meet all codes per ANSI for cab deflection. |
| DESIGN | Floor loading or Counter height |
| CAR | 28"x28"x28" or Custom Size and Shape |
| SIZE | Up to 15.63 ft cubed |
| MATERIAL | 12 Ply Russian birch steel or Stainless Steel |
| OPENING | One, two or three sides available. |
| CAPACITY | 250 lbs |
| SPEED | 30 fpm |
| POWER | 115v 15 AMP |
| POWER UNIT | Underneath, or adjacent to shaft. |
| WINDING DRUM | High torque electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/8" x 7 x 19 improved plow stainless steel cable. |
| GUIDE RAIL | Monorail type |
| CONTROLS | Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided for top final. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at the landing. |
| CONTROLLER | 9" wide x 13" tall x 4" deep |
| OPTIONAL EQUIPMENT | Light in car, sound base, Roll top gate, removable adjustable shelves, 3" retaining lip on opening. |