



Elevation Innovation Inc.
6200 Enterprise Dr Suite H
Diamond Springs, CA 95619
Phone: 877-345-4387
Fax: 877-285-3050

Inteli-Lift 250 dumbwaiter specifications

UL Listing #SA32120

Deflection 250# dumbwaiter will carry 250 lbs and meet all codes per ANSI for cab deflection.

DESIGN Floor loading or Counter height

CAR 28"x28"x28" or Custom Size and Shape

SIZE Up to 15.63 ft cubed

MATERIAL 12 Ply Russian birch or Stainless Steel

OPENING One, two or three sides available.

CAPACITY 250 lbs

SPEED 30 fpm

POWER 110v 15 AMP

POWER UNIT Underneath, or adjacent to shaft.

WINDING DRUM High torque electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/8" x 7 x 19 improved plow stainless steel cable.

GUIDE RAIL Monorail type

CONTROLS Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided for top final. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at the landing.

OPTIONAL EQUIPMENT Light in car, sound base, Roll top gate, removable adjustable shelves, 3" retaining lip on opening.