



Elevation Innovation Inc.
6200 Enterprise Dr Suite H
Diamond Springs, CA 95619
Phone: 877-345-4387
Fax: 877-285-3050

Inteli-Lift 500 dumbwaiter specifications

Deflection	500# dumbwaiter will carry 500 lbs and meet all codes per ANSI for cab deflection.
DESIGN	Floor loading or Counter height
CAR	36" x 36" x 48" or Custom Size and Shape
SIZE	Up to 36 ft cubed
MATERIAL	Mild steel powder coated, Stainless Steel or Anodized aluminum in a knock down cab
OPENING	One, two sides available.
CAPACITY	500 lbs
SPEED	30 fpm
POWER	230v 6.4 AMP
POWER UNIT	Underneath, Overhead or adjacent to shaft.
WINDING DRUM	High torque electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/4" x 7 x 19 improved plow stainless steel cable.
GUIDE RAIL	Monorail type
CONTROLS	Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided top and bottom. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at the landing. Light in car.