



Elevation Innovation Inc.
6200 Enterprise Dr Suite H
Diamond Springs, CA 95619
Phone: 877-345-4387
Fax: 877-285-3050

Inteli-Lift 75 dumbwaiter specifications

UL Listing #SA32120

Deflection	75# dumbwaiter will carry 75 lbs and meet all codes per ANSI for cab deflection.
DESIGN	Floor loading or Counter height
CAR	18"x18"x24" or Custom Size and Shape
SIZE	Up to 4.5 ft cubed
MATERIAL	12 Ply Russian birch or Stainless Steel
OPENING	One, two or three sides available.
CAPACITY	75 lbs
SPEED	30 fpm
POWER	110v 15 AMP
POWER UNIT	Underneath, or adjacent to shaft.
WINDING DRUM	High torque electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/8" x 7 x 19 improved plow stainless steel cable.
GUIDE RAIL	Monorail type
CONTROLS	Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided for top final. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at the landing.
OPTIONAL EQUIPMENT	Light in car, sound base, Roll top gate, removable adjustable shelves, 3" retaining lip on opening.