



Elevation Innovation Inc.
6048 Enterprise Dr Suite A
Diamond Springs, CA 95619
Phone: 530-295-4900
Fax: 877-285-3050

Inteli-Lift RST Stainless Cab Specifications

UL Listing #SA32120

CAB SIZE	20" wide x 30" deep x 36" tall or Custom Size and Shape
MATERIAL	16 gauge 304 Stainless Steel with a #4 finish
DEFLECTION	250# dumbwaiter will carry 250 lbs and meet all codes per ANSI for cab deflection
DESIGN	Solid stainless steel fully welded joints and reinforced with 1" x 1" x 1/8" angle
OPENING	One, two or three sides available.
GATE	Extruded aluminum roll up gate
CAPACITY	250 lbs

-----System Specifications-----

SPEED	30 fpm
POWER	110v 15 AMP
POWER UNIT	Underneath, or adjacent to shaft
WINDING DRUM	High torque electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/8" x 7 x 19 improved plow stainless steel cable
GUIDE RAIL	Monorail type
CONTROLS	Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided for top final. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at the landing
CONTROLLER	9" wide x 13" tall x 4" deep
OPTIONAL EQUIPMENT	Light in car, sound base, Roll top gate, removable adjustable shelves, 3" retaining lip on opening